



ROLLER DOOR OPERATOR



The KJ500, KJ600 and KJ1000 rolling door operators are designed to drive rolling door (rolling shutter) from 500kg to 1000kg. The products featured with powerful starting strength, overworking for a short time and overheat protection when overloaded. In case of power failure, a release chain can be used to operate door manually.

Advanced Features

- ◆ Powerful starting strength, loading up to 1000kg
- ◆ KJ500 C with battery backup in case of power cuts
- ◆ Available in 3-phase (KJ1000)
- ◆ Overworking for a short time
- ◆ Overheat protection
- ◆ Limit switch enables precise adjustment in up and down positions
- ◆ Electric and manual operations
- ◆ Release chain in case of power failure
- ◆ Built-in control panel (JM500, KJ500C & KJ600C)
- ◆ Wiring terminals for photocells, alarm lamp and remote controller
- ◆ Safety lock device prevents vehicle or people from damage in case of roller chain is break off

KJ500DC / KJ600



KJ1000



Model	KJ 500 DC	KJ 600	KJ 1000
Power supply	220V, 50 Hz	220 V, 50 Hz	380V-220V, 50Hz 3 phase
Motor speed	1250 rpm	1250 rpm	1250 rpm
Rated power	370W	370W	500W
Rated current	4.0A	4.0A	1.2A
Max. Lifting load	500 kg	600 kg	1000 kg
Roller diameter	128 mm	128 mm	154 mm
Roller rotate	5.7 rpm	6.5 rpm	5.5 rpm
Chain spec.	10A 1x66	10A 1x74	12A 1x76